

Dockerfiles

- [IIS - Default](#)
- [IIS - WCF](#)

IIS - Default

Dockerfile

```
FROM mcr.microsoft.com/windows/servercore/iis
RUN powershell -NoProfile -Command Remove-Item -Recurse C:\inetpub\wwwroot\*
RUN powershell Remove-WebSite -Name 'Default Web Site'
RUN powershell Import-Module WebAdministration;New-Item -Path IIS:\AppPools\WWWPool;New-
Item -Path $env:systemdrive\inetpub\www -Type Directory;New-Item -Path
$env:systemdrive\inetpub\XpServerDllFiles -Type Directory;New-WebSite -Name XpNDFAsiaSite -
Port 4847 -PhysicalPath "$env:systemdrive\inetpub\www" -ApplicationPool WWWPool -Force;

WORKDIR /inetpub/www
COPY content/ .

EXPOSE 4847
```

Build-Batch

```
@echo off
docker build -t myiis:v1.0 .
```

IIS - WCF

Dockerfile

```
FROM mcr.microsoft.com/dotnet/framework/wcf:4.8-windowsservercore-ltsc2016

RUN mkdir VSS2005
COPY VSS2005 VSS2005
RUN c:\windows\system32\regsvr32.exe /i /s c:\VSS2005\ssapi.dll

WORKDIR /inetpub/wwwroot
RUN C:\Windows\System32\inetsrv\appcmd set apppool /apppool.name:DefaultAppPool
/enable32BitAppOnWin64:true
#COPY C:\VSProjects\VSSx86\_publish\_PrecompiledWeb\wcfVssNet .
COPY wcfVssNet .

Build-Batch

@echo off
docker build -t wcfvssnet.v2.0:sac2016 .
```